



RIDUZIONE 3/4 > 1/2 PRESENTE NELLA CONFEZIONE  
 REDUCTION 3/4 > 1/2 IN THIS PACKAGE

scheda tecnica

technical data

## 45950

Miscelatore termostatico incasso con rubinetto d'arresto  
 Concealed thermostatic valve with volume control

Cromo, Bianco, Nero  
 Chrome, White, Black

- Termostatico con comando a leva
- Cartuccia termostatica certificata - Vernet
- Cartuccia con funzione anti scottatura e anti calcare
- Vitone con dischi ceramici 3/4 90° - certificato
- Attacchi all' impianto idrico G3/4
- Attacco uscita doccia G3/4
- Piastra con rosone scorrevole
- Temperatura acqua impostata a 38°
- Regolazione portata
- Plaster di riferimento per installazione
- Protezione in polistirolo antirumore e vibrazione
- Disponibile kit prolunga
- Garanzia 5 anni

- Thermostatic with lever
- Thermostatic certificate cartridge - Vernet
- Cartridge with anti-scald and antilimescale function
- G3/4 90° screw with ceramic discs - certificate
- Water supply connection G3/4
- Water shower connection G3/4
- Plate with swivel rosette
- Water temperature set to 38°
- Flow rate regulation
- Plaster of reference for installation
- Polystyrene protection anti noise and vibration
- Available extension kit
- 5 years guarantee

- Portata 40 litri/min (3 bar)

- Flow rate 40 liters/min (3bar)

- Riferimenti normative:
- EN 817
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817
- Resistance surface coating Ni-Cr in according EN 248

- Certificazioni disponibili: ASME/CSA (per la parte incasso)

- Available certification: ASME/CSA (for concealed parts)

**LA TORRE srl**  
 28045 Inverio - (NO)  
 Via Altovergante, 33  
 ITALY



Tel. +39 0322 255391 r.a.  
 Fax +39 0322 255442  
[www.rubinetteria-latorre.it](http://www.rubinetteria-latorre.it)  
[info@rubinetteria-latorre.it](mailto:info@rubinetteria-latorre.it)



rev0\_06.2015



Con riserva di modifiche - Subject to change



45950 ita\_eng\_rev0