



RIDUZIONE 3/4 > 1/2 PRESENTE NELLA CONFEZIONE
REDUCTION 3/4 > 1/2 IN THIS PACKAGE

scheda tecnica

technical data

45950 R2

Miscelatore termostatico incasso con deviatore a 2 uscite
Concealed thermostatic valve with diverter two out

Cromo, Bianco, Nero, Finitura acciaio
Chrome, White, Black, Inox fishing

- Termostatico con comando a leva
- Cartuccia termostatica Vernet certificata, con funzione anti scottatura e anti calcare, temperatura acqua impostata a 38°
- Rubinetto prodotto completamente in ottone
- Attacchi all' impianto idrico e uscita doccia G3/4
- Piastra con rosone scorrevole
- Deviatore a dischi ceramici 2 uscite con comando a maniglia
- Valvole di non ritorno attivabili per eventuali manutenzioni
- Plaster di riferimento per installazione
- Protezione in polistirolo antirumore e vibrazione
- Disponibile kit prolunga
- Garanzia 5 anni

- Thermostatic with lever
- TVernet thermostatic cartridge (certificated), with anti-scald and antilimescale function. Water temperature settin at 38°
- Completely made in brass
- Water supply connection and outlet connection G3/4,
- Plate with swivel rosette
- 2 ways handle diverter with ceramic discs
- Check valves with possibility to actuated for maintenance
- Plaster of reference for installation
- Polystyrene protection anti noise and vibration
- Available extension kit
- 5 years guarantee

- Portata 30 litri/min (3 bar)

- Flow rate 30 liters/min (3bar)

- Riferimenti normative:
- EN 817
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817
- Resistance surface coating Ni-Cr in according EN 248

- Certificazioni disponibili: ASME/CSA (solo valvola termostatica)
- Available certification: ASME/CSA (only for thermostatic valve)

LA TORRE srl
28045 Inverio - (NO)
Via Altovergante, 33
ITALY



Tel. +39 0322 255391 r.a.
Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev0_06.2015



Con riserva di modifiche - Subject to change



45950 R2 ita_eng_rev0