



scheda tecnica

technical data

## 40036 COL

Monocomando esterno doccia con colonna doccia.  
Single lever external shower mixer with shower column.

Cromo  
Chrome

- Miscelatore con comando a leva
- Cartuccia diametro 35 con dischi in ceramica con possibilità di regolazione della temperatura e portata KN 35B HWS - Kerox
- Non disponibile cartuccia con sistema ECO
- Leva in zama
- Rosoni in ottone G3/4
- Attacchi all'impianto idrico G1/2
- Flessibile ottone con gomma atossica
- Doccetta ABS con gomma anticalcare
- Soffione con valvola regola flusso 12 l/min
- Colonna doccia con deviatore integrato soffione/doccetta
- Colonna doccia regolabile in altezza
- Garanzia 5 anni

- Mixer with lever
- 35 diameter cartridge with ceramic disc with temperature and flow limiting device KN 35B HWS - Kerox
- Not available on request ECO cartridge
- Zamak lever
- Brass rosette G3/4
- Water supply connections G1/2
- Brass flex hose with atossic rubber
- ABS headshower with antilime rubber
- Showerhead with flow rate valve 12 l/min
- Shower column with diverter shower head / shower
- Adjustable shower column height
- 5 years guarantee

- Portata 12 litri/min (3 bar) uscita soffione
- Portata 12 litri/min (3 bar) uscita doccetta

- Flow rate 12 liters/min (3bar) showerhead outlet
- Flow rate 12 liters/min (3bar) hand shower outlet

- Riferimenti normative:
- EN 817 - EN32
- EN 248

- Reference standards:
- EN 817 - EN32
- EN 248

- Foratura piano (mm): max40

- Drilling plan (mm): max40

**LA TORRE srl**  
28045 Inverio - (NO)  
Via Altovergante, 33  
ITALY

Tel. +39 0322 255391 r.a.  
Fax +39 0322 255442  
[www.rubinetteria-latorre.it](http://www.rubinetteria-latorre.it)  
[info@rubinetteria-latorre.it](mailto:info@rubinetteria-latorre.it)

