



scheda tecnica

technical data

## 44950 MULTI 3

Doccia incasso termostatico a 3 uscite indipendenti e/o simultanee  
Thermostatic shower unit with 3 independent and/or simultaneous exit

Cromo  
Chrome

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>Miscelatore termostatico incasso per doccia multi uscita</li> <li>Vitoni GN90 G1/2 a dischi ceramici con apertura a 90° (certificato)</li> <li>Cartuccia termostatica Vernet certificata, con funzione anti scottatura e anti calcare, temperatura acqua impostata a 38°</li> <li>Attacchi all' impianto idrico G1/2-G3/4</li> <li>Attacchi in uscita G1/2</li> <li>Valvole di non ritorno attivabili per eventuali manutenzioni</li> <li>Rubinetto e maniglie in ottone, piastra in acciaio</li> <li>Piastra con rosone scorrevole</li> <li>Protezione in polistirolo antirumore e antivibrazione</li> <li>Garanzia 5 anni</li> </ul> | <ul style="list-style-type: none"> <li>Thermostatic shower mixer with multi outlets</li> <li>GN90 G1/2 headworks with ceramics discs, 90° opening range (certificated)</li> <li>Vernet thermostatic cartridge (certificated), with anti-scald and antilimescale function. Water temperature settin at 38°</li> <li>Water supply connection G1/2-G3/4</li> <li>Outlet connction G1/2</li> <li>Check valves with possibility to actuated for maintenance</li> <li>Tap and handles completely made in brass, plate made in steel</li> <li>Plate with sliding rosettes</li> <li>Polystyrene protection anti noise and anti vibration</li> <li>5 years guarantee</li> </ul> |
| <ul style="list-style-type: none"> <li>Portata 27 litri/min (3 bar)</li> </ul>  | <ul style="list-style-type: none"> <li>Flow rate 27 liters/min (3bar)</li> </ul>   |
| <ul style="list-style-type: none"> <li>Riferimenti normative:</li> <li>EN 817 - EN32</li> <li>Rivestimento superficiale Ni-Cr a norma EN 248</li> </ul>   | <ul style="list-style-type: none"> <li>Reference standards:</li> <li>EN 817 - EN32</li> <li>Resistance surface coating Ni-Cr in according EN 248</li> </ul>  |
| <ul style="list-style-type: none"> <li>Certificazioni disponibili: ASME/CSA (solo valvola termostatica)</li> </ul>  | <ul style="list-style-type: none"> <li>Available certification: ASME/CSA (only for thermostatic valve)</li> </ul>  |

LA TORRE srl  
28045 Inverio - (NO)  
Via Altovergante, 33  
ITALY



Tel. +39 0322 255391 r.a.  
Fax +39 0322 255442  
www.rubinetteria-latorre.it  
info@rubinetteria-latorre.it



rev0\_07.2017



Con riserva di modifiche - Subject to change



44950 MULTI 3 ita\_eng\_metric\_rev0