



scheda tecnica

technical data

46001 CS

Monocomando lavabo con scarico e flex inox.
Lavatory mixing faucet, with pop-up waste and flex inox.

Cromo, Bianco o Nero, Finitura Acciaio
Chrome, White/Black, Inox finishing

- Lavabo con comando a leva
- Cartuccia D25 tipo aperto con dischi ceramici K25-OP QMET - KEROX
- Non disponibile cartuccia con sistema ECO
- Aeratore rettangolare PL-RC 28x7 V con chiave di smontaggio - NEOPERL
- Leva zama
- Scarico G1¼ con piletta ottone - certificato NF
- Asta per scarico a movimento verticale
- Fissaggio con tiranti M6
- Attacchi all' impianto idrico G3/8
- Flex inox di collegamento SOFTPEX DN6 CM50 - NEOPERL
- Regolazione portata con valvole PCW 3 L/MIN - NEOPERL
- Garanzia 5 anni

- Mixer with lever
- 25 diameter cartridge open type with ceramic disc K25-OP QMET - KEROX
- Not available on request ECO cartridge
- Aerator rectangular PL-RC 28x7 V with disassembly key - NEOPERL
- Zamak lever
- G1¼ pop-up waste with brass waste - NF certificate
- Rod for pop-up waste vertical movement
- Fixed with rod nut M6
- Water supply connections G3/8
- Flex inox connections SOFTPEX DN6 CM50 - NEOPERL
- Flow rate regulation with valve PCW 3 L/MIN - NEOPERL
- 5 years guarantee

- Portata 6 litri/min (3 bar)

- Flow rate 6 liters/min (3bar)

- Riferimenti normative:
- EN 817 - EN32
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817 - EN32
- Resistance surface coating Ni-Cr in according EN 248

- Forature piano (mm):
- min34 max37

- Drilling plan (mm):
- min34 max37

LA TORRE srl
28045 Inverio - (NO)
Via Altovergante, 33
ITALY



Tel. +39 0322 255391 r.a.
Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev0_05.2017



Con riserva di modifiche - Subject to change



46001CS ita_eng_rev0