



scheda tecnica

technical data

## 45050R 16

Monocomando incasso doccia con deviatore a ritorno automatico  
Built - in shower mixer with automatic return diverter

Cromo, Bianco, Nero, Finitura Acciaio  
Chrome, White, Black, Inox Finishing

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>• Miscelatore con comando a leva</li> <li>• Cartuccia diametro 35 tipo chiuso con dischi in ceramica con limitatore portata e temperatura KN-35B HWS - Kerox</li> <li>• Non disponibile cartuccia versione ECO</li> <li>• Corpo con alette di fissaggio per flessibilità di installazione</li> <li>• Attacchi all' impianto idrico G1/2</li> <li>• Leva in zama</li> <li>• Piastra ottone scorrevole con rosone di fissaggio</li> <li>• Corpo miscelatore in ottone stampato</li> <li>• Deviatore a pulsante Neoperl con ritorno automatico</li> <li>• Pressione minima funzionamento deviatore 0.7bar</li> <li>• Garanzia 5 anni</li> </ul> | <ul style="list-style-type: none"> <li>• Mixer with lever</li> <li>• 35 diameter cartridge with ceramic disc with temperature and flow limiting device KN-35B HWS - Kerox</li> <li>• Not available cartridge ECO version</li> <li>• Concealed part with fastening tabs for easiness installation</li> <li>• Water connections G1/2</li> <li>• Zamak lever</li> <li>• Swivel brass plate with rosette fixing</li> <li>• Body of mixer in forged brass</li> <li>• Neoperl button diverter with automatic return</li> <li>• Minimum pressure of diverter operation 0.7bar</li> <li>• 5 years guarantee</li> </ul> |
| <ul style="list-style-type: none"> <li>• Portata 21 litri/min (3 bar) uscita doccia</li> <li>• Portata 21 litri/min (3 bar) uscita vasca</li> </ul>   | <ul style="list-style-type: none"> <li>• Flow rate 21 liters/min (3bar) outlet shower</li> <li>• Flow rate 21 liters/min (3bar) outlet bath</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Riferimenti normative:</li> <li>• EN 817</li> <li>• Rivestimento superficiale Ni-Cr a norma EN 248</li> </ul>  | <ul style="list-style-type: none"> <li>• Reference standards:</li> <li>• EN 817</li> <li>• Resistance surface coating Ni-Cr in according EN 248</li> </ul>   |
| <ul style="list-style-type: none"> <li>• Forature piano (mm):</li> <li>• max50+45</li> </ul>  | <ul style="list-style-type: none"> <li>• Drilling plan (mm):</li> <li>• max50+45</li> </ul>  |

LA TORRE srl  
28045 Inverio - (NO)  
Via Altovergante, 33  
ITALY



Tel. +39 0322 255391 r.a.  
Fax +39 0322 255442  
[www.rubinetteria-latorre.it](http://www.rubinetteria-latorre.it)  
[info@rubinetteria-latorre.it](mailto:info@rubinetteria-latorre.it)



rev0\_06.2015



Con riserva di modifiche - Subject to change



45050R 16 ita\_eng\_rev0