



scheda tecnica

technical data

45050RL 16

Monocomando incasso doccia con deviatore a leva
Built - in shower mixer with lever diverter

Cromo, Bianco, Nero, Finitura Acciaio
Chrome, White, Black, Inox Finishing

- | | |
|---|---|
| <ul style="list-style-type: none"> • Miscelatore con comando a leva • Cartuccia diametro 35 con dischi ceramici Kerox KN-35B HWS • Corpo con alette di fissaggio per flessibilità di installazione • Attacchi all' impianto idrico G1/2 • Leva zama • Piastra ottone scorrevole con rosone di fissaggio • Corpo miscelatore in ottone stampato • Deviatore a comando rotativo non automatico, funzionante e manovrabile a tutte le pressioni • Garanzia 5 anni | <ul style="list-style-type: none"> • Mixer with lever • 35 diameter cartridge with ceramic disc, Kerox KN-35B HWS • Concealed part with fastening tabs for easiness installation • Water supply connections G1/2 • Zamak lever • Swivel brass plate with rosette fixing • Body of mixer in forged brass • Rotary manual diverter. Working and usable at all values of pressure • 5 years guarantee |
| <ul style="list-style-type: none"> • Portata 18 litri/min (3 bar) uscita doccia • Portata 18 litri/min (3 bar) uscita vasca | <ul style="list-style-type: none"> • Flow rate 18 liters/min (3bar) outlet shower • Flow rate 18 liters/min (3bar) outlet bath |
| <ul style="list-style-type: none"> • Riferimenti normative: • EN 817 • Rivestimento superficiale Ni-Cr a norma EN 248 | <ul style="list-style-type: none"> • Reference standards: • EN 817 • Resistance surface coating Ni-Cr in according EN 248 |
| <ul style="list-style-type: none"> • Forature piano (mm): • max50+45 | <ul style="list-style-type: none"> • Drilling plan (mm): • max50+45 |

LA TORRE srl
28045 Invorio - (NO)
Via Altovergante, 33
ITALY



Tel. +39 0322 255391 r.a.
Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev0_06.2015



Con riserva di modifiche - Subject to change



45050RL 16 ita_eng_rev0