



RIDUZIONE 3/4 > 1/2 PRESENTE NELLA CONFEZIONE
 REDUCTION 3/4 > 1/2 IN THIS PACKAGE

scheda tecnica

technical data

45955

Miscelatore termostatico incasso 3/4
 Concealed thermostatic valve 3/4

Cromo, Bianco, Nero
 Chrome, White, Black

- Termostatico con comando a leva
- Cartuccia termostatica certificata - Vernet
- Cartuccia con funzione anti scottatura e anti calcare
- Attacchi all' impianto idrico G3/4
- Attacco uscita doccia G3/4
- Piastra con rosone scorrevole
- Temperatura acqua impostata a 38°
- Plaster di riferimento per installazione
- Protezione in polistirolo antirumore e vibrazione
- Disponibile kit prolunga
- Garanzia 5 anni

- Thermostatic with lever
- Thermostatic certificate cartridge - Vernet
- Cartridge with anti-scald and antilimescale function
- Water supply connection G3/4
- Water shower connection G3/4
- Plate with swivel rosette
- Water temperature set to 38°
- Plaster of reference for installation
- Polystyrene protection anti noise and vibration
- Available extension kit
- 5 years guarantee

- Portata 60 litri/min (3 bar)

- Flow rate 60 liters/min (3bar)

- Riferimenti normative:
- EN 817
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817
- Resistance surface coating Ni-Cr in according EN 248

- Certificazioni disponibili: ASME/CSA (per la parte incasso)

- Available certification: ASME/CSA (for concealed parts)

LA TORRE srl
 28045 Inverio - (NO)
 Via Altovergante, 33
 ITALY



Tel. +39 0322 255391 r.a.
 Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev0_06.2015



Con riserva di modifiche - Subject to change



45955 ita_eng_rev0