



scheda tecnica

technical data

## 26020

Monocomando esterno vasca con supporto doccia regolabile  
Single lever external bath mixer with adjustable shower bracket

Cromo, Finitura Acciaio  
Chrome, Finishing inox

- Miscelatore con comando a leva
- Cartuccia diametro 35 con dischi in ceramica con possibilità di regolazione della temperatura e portata NKJ35A HWS
- Aeratore Neoperl Slim M24x1 + c hiave di smontaggio
- Leva zama
- Deviatore vasca/doccia con blocco manuale
- Rosone ottone
- Attacchi all' impianto idrico G1/2
- Attacco uscita doccia G1/2
- Doccetta ABS con gomma anticalcare - monogetto
- Flessibile PVC con gomma atossica
- Supporto ABS a muro fisso per doccetta
- Supporto OTTONE a muro regolabile per doccetta
- Garanzia 5 anni

- Mixer with lever
- 35 diameter cartridge with ceramic discs with temperature and flow limiting device NKJ35A HWS
- Aerator Neoperl Slim 24x1 + disassembly key
- Zamak lever
- Bath/shower diverter with stop
- Brass rosette
- Water supply connection G1/2
- Water shower connection G1/2
- ABS headshower with antilime rubber - single spray
- PVC flex hose with atossic rubber
- ABS fix wall bracket for hand shower
- BRASS adjustable wall bracket for hand shower
- 5 years guarantee

- Portata 12 litri/min (3 bar) doccia
- Portata 30 litri/min (3 bar) vasca

- Flow rate 12 liters/min (3bar) shower
- Flow rate 30 liters/min (3bar) bath

- Riferimenti normative:
- EN 817
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817
- Resistance surface coating Ni-Cr in according EN 248

- Foratura piano (mm): max40

- Drilling plan (mm): max40

LA TORRE srl  
28045 Inverio - (NO)  
Via Altovergante, 33  
ITALY



Tel. +39 0322 255391 r.a.  
Fax +39 0322 255442  
www.rubinetteria-latorre.it  
info@rubinetteria-latorre.it

