



scheda tecnica

technical data

## 42020

Monocomando esterno vasca con gancio a muro regolabile  
Single lever external bath mixer with adjustable wall bracket

Cromo  
Chrome

- Monocomando con comando a leva
- Cartuccia diametro 35 tipo chiuso con dischi in ceramica senza limitatore di temperatura e portata K2 35W-B - Kerox
- Aeratore M24x1 D - Neoperl
- Leva zama
- Deviatore vasca/doccia con blocco manuale
- Rosone ottone G3/4
- Gambo eccentrico G3/4 - G1/2
- Attacchi all'impianto idrico G1/2
- Attacco flessibile doccia G1/2
- Flessibile treccia ottone con gomma atossica
- Supporto per doccetta in ABS snodato
- Doccetta monogetto con gomma anticalcare
- Garanzia 5 anni

- Mixer with lever
- 35 diameter cartridge with ceramic disc without possibility to regulate the temperature and flow K2 35W-B - Kerox
- Aerator M24x1 D - Neoperl
- Zamak lever
- Bath/shower diverter with stop
- Brass rosette G3/4
- Eccentric joint G3/4 - G1/2
- Water supply connections G1/2
- Flex hose shower connection G1/2
- Brass flex hose with atossic rubber
- ABS wall swivel support for handshower
- Handshower single-spray with antilime
- 5 years guarantee

• Portata 20 litri/min (3 bar)

• Flow rate 20 liters/min (3bar)

- Riferimenti normative:
- EN 817
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817
- Resistance surface coating Ni-Cr in according EN 248

**La Torre srl**  
28045 Inverio - No  
Via Altovergante, 33  
ITALY

Tel. +39 0322 255391 r.a.  
Fax +39 0322 255442  
**www.rubinetteria-latorre.it**  
**info@rubinetteria-latorre.it**

