



scheda tecnica

technical data

12045

Monocomando bordo vasca 3 fori.
Single lever mixer for bathtub edge.

Cromo
Chrome

- Miscelatore con comando a leva
- Cartuccia diametro 35 con dischi in ceramica con possibilità di regolazione della temperatura e portata NKJ35A HWS
- Aeratore Neoperl HoneyComb M28x1D
- Bocca fissa
- Flex inox di collegamento all'impianto idrico G3/8" cm50
- Deviatore bocca/doccetta con blocco
- Doccetta ABS con gomma anticalcare - monogetto
- Flessibile ottone con gomma atossica
- Garanzia 5 anni

- Mixer with lever
- 35 diameter cartridge with ceramic disc with temperature and flow limiting device NKJ35A HWS
- Aerator Neoperl HoneyComb M28x1D
- Fixed spout
- Water supply connections flex inox G3/8" cm50
- Diverter spout/shower with stop position
- ABS headshower with antilime rubber - single spray
- Brass flex hose with atossic rubber
- 5 years guarantee

- Portata 18.5 litri/min (3 bar) uscita bocca
- Portata 10.5 litri/min (3 bar) uscita doccetta

- Flow rate 18.5 liters/min (3bar) outlet spout
- Flow rate 10.5 liters/min (3bar) outlet shower

- Riferimenti normative:
- EN 817 - EN32
- Rivestimento superficiale Ni-Cr a norma EN 248

- Reference standards:
- EN 817 - EN32
- Resistance surface coating Ni-Cr in according EN 248

- Foro ceramica miscelatore: min.40 mm - max.42 mm
- Foro ceramica bocca: min.34 mm - max.37 mm
- Foro ceramica doccetta: min.31 mm - max.37 mm

- Ceramic hole diameter for mixer: min.40 mm - max.42 mm
- Ceramic hole diameter for spout: min.34 mm - max.37 mm
- Ceramic hole diameter for shower: min.31 mm - max.37 mm

LA TORRE srl
28045 Inverio - (NO)
Via Altovergante, 33
ITALY



Tel. +39 0322 255391 r.a.
Fax +39 0322 255442
www.rubinetteria-latorre.it
info@rubinetteria-latorre.it



rev1_11.2017



Con riserva di modifiche - Subject to change



12045 ita_eng_metric_rev1